

Product Specification Sheet

Tyvek Packed 100g Humidity Balance Sachet

Product Tyvek Packed 100g Humidity Balance Sachet (RH62%)

Raw Material sodium chloride、 calcium chloride、 silicon dioxide、 water

Packaging Material Tyvek

Technical Standard

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Humidity regulator range 25°C	62% ± 5%
Balance time	≤ 24h
Dropping resistance	In the case of free falling of 15 times at a height of 1.2m or more, the sachet bag shall not be broken.
Decoloring test	The soaked solution should be colorless.
* Lead	≤ 5ppm
Total bacterial count (cfu / bag)	≤ 10 ³
Mould and yeast count (cfu / bag)	≤ 10 ²
Escherichia coli	Not detectable per bag

Sachet Dimension
 Net Weight: 95~110g
 Width: 98±4mm
 Length: 130±6mm

Sealing Method back seal

—30pcs/foil bag 120pcs/4foil bags/carton
 foil bag: 300×400, 10s
 Carton Size: 370×275×250 mm, 48ctns/pallet

STD Packaging —Carton label contains the following:
 PO Number
 Product Name
 Specification
 Quantity
 Batch Number
 MADE IN CHINA



Product Specification Sheet

Tyvek Packed 100g Humidity Balance Sachet

Storage The shelf life of unopened product is 1 year ,at 15 ~ 35°C ,RH 30% ~ 70%

Notes The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2020-11-18

